

# XSEDE Data Management Use Cases

April 24, 2013

Version 1.5



## Table of Contents

- [A Document History](#)
- [B Document Scope](#)
- [C Summary of Data Movement Use Cases](#)
- [D Data Movement Use Cases](#)



## A. Document History

---

### Overall Document Authors:

Christopher Jordan  
Texas Advanced Computing Center  
The University of Texas at Austin  
Austin, TX  
ctjordan@tacc.utexas.edu

Kurt Seiffert  
Indiana University  
Bloomington, Indiana  
seiffert@iu.edu

Altaf Hossain  
Pittsburgh Supercomputing Center (PSC)  
Pittsburgh, PA  
altaf@psc.edu

Ian Foster  
The University of Chicago and Argonne National Laboratory  
Argonne, IL 60439  
foster@anl.gov

Morris Riedel Jülich Supercomputing Centre  
Forschungszentrum Jülich GmbH  
D-52425 Jülich  
Germany

Andrew Grimshaw  
University of Virginia  
PO Box 400740  
Charlottesville VA 22904  
grimshaw@virginia.edu

David Lifka  
Cornell University  
512 Frank H. T. Rhodes Hall  
Ithaca, NY 14853  
lifka@cac.cornell.edu

---



Description	Version	Date	Changes	Author
First formatted and accepted version	1.5	4/23/2013	Full text	Altaf Hossein, Chris Jordan

## B. Document Scope

---

This document is both a user-facing document (publically accessible) and an internal working document intended to define user needs and use cases that fall under the general umbrella of Data Management within the overall activities of XSEDE. The definition of use cases is based on a template from Malan and Bredemeyer<sup>1</sup>. In general it is in keeping with the approaches and philosophy outlined in “Software architecture in practice.”<sup>2</sup>

This document is one component of a process that generates at least the following documents, some of which are user-facing, some are as of now intended to be internal working documents:

- ***This document*** - A description of use cases [User facing]
- A binary mapping of use cases to Requirements in DOORS (a binary mapping – for each use case a “yes” or “no” flag indicating whether a particular requirement within the full list of requirements is or is not required to enable a particular use case)
- A set of level 3 decomposition documents, which include:
  - Quality Attributes descriptions
  - Connections diagram in UML

The use cases are presented here using the following format, derived from the Malan and Bredemeyer white paper<sup>1</sup> as follows:

Use Case	Use case identifier and reference number and modification history
<i>Description</i>	Goal to be achieved by use case and sources for requirement
<i>References</i>	References and citations relevant to use case
<i>Actors</i>	List of actors involved in use case
<i>Prerequisites (Dependencies)</i>	Conditions that must be true for use case to be possible

---

<sup>1</sup> Malan, R., and D. Bredemeyer. 2001. Functional requirements and use cases. [www.bredemeyer.com/pdf\\_files/functreq.pdf](http://www.bredemeyer.com/pdf_files/functreq.pdf)

<sup>2</sup> Bass, L., P Paul Clements, and Rick Kazman

---

<i>&amp; Assumptions</i>	Conditions that must be true for use case to terminate successfully
<i>Steps</i>	Interactions between actors and system that are necessary to achieve goal
<i>Variations (optional)</i>	Any variations in the steps of a use case
<i>Quality Attributes</i>	
<i>Non-functional (optional)</i>	List of non-functional requirements that the use case must meet
<i>Issues</i>	List of issues that remain to be resolved

### C. **Summary of Data Management Use Cases**

---

The Data Management use cases cover a broad range of activities related to data movement, storage, and archival by users and communities of users in the context of XSEDE. These include interactions with data collections created outside of XSEDE, data collections created using XSEDE resources, and communities and collections crossing the boundary of XSEDE to include campus-level resources. The current use cases cover basic data sharing by a user community (UCDM1.0), execution of a coordinated program of research using a shared data collection (UCDM2.0), and a coordinated program of research utilizing data generated by a sensor or network of sensors on a regular or continuous basis (UCDM3.0). Future use cases will address migration of a users data in association with a change of primary computational activity or a change of service provider status (UCDM 4.0), and creation, access, and search of metadata associated with a data collection (UCDM5.0).

---

### D. **Data Management Use Cases**

---

<b>Use Case 1.0</b>	<b>UCDM1.0: Share and manage a common repository of data with a distributed</b>
---------------------	---------------------------------------------------------------------------------

---



	user community
<i>Description</i>	A group of users, individually or collectively, build a collection of data and software code, which must be shared with and managed by a community of users using many XSEDE resources.
<i>References</i>	References and citations relevant to use case: TBD.
<i>Actors</i>	<p>Collection Manager: A user with elevated privileges to deposit and manage data in the collection.</p> <p>Collection User: A user with limited privileges to access data and code in the collection.</p> <p>User Agent: A script or function that acts on behalf of a user on one or more XSEDE resources.</p> <p>Collective-User Agent: A script or function that acts on behalf of the group of users, typically to perform regular curation tasks.</p> <p>Data gateway: A system or service that provides open access to a shared collection of data to users outside of the set of XSEDE resources</p>
<i>Prerequisites (Dependencies) &amp; Assumptions</i>	<p>All users of the shared data collection have XSEDE or other identities that can be used to set and enforce permissions.</p> <p>Users will have differing levels of privilege to create and/or alter data within the collection.</p> <p>All computational and login systems on which users access data are within the XSEDE “circle of trust” and use the XSEDE accounting system to exchange information regarding usage, accounts, and allocations.</p>
<i>Steps</i>	<ol style="list-style-type: none"> <li>1. Collection Manager logs in to an XSEDE resource</li> <li>2. The Collection Manager moves (or copies) data from a local data resource into a shared resource using local data movement tools</li> <li>3. The Collection Manager alters the structure of the collection (directory hierarchies, file locations) as appropriate for collective data sharing</li> <li>4. The Collection Manager sets permissions on components of the collection to allow for public, semi-public, and private use of data by relevant actors</li> <li>5. A Collection User logs in to (the same or a different) XSEDE resource</li> <li>6. The Collection User copies data from the shared collection area into a local storage resource for use in computation or analysis tasks</li> <li>7. The Collection user performs computation or analysis resulting in data for further sharing</li> <li>8. The Collection user moves (or copies) their result data into the shared</li> </ol>

	collection area for use by others
<i>Variations (optional)</i>	<p>1. Instead of Collection Managers and users directly logging in to XSEDE resources to access data, they could use remote data transfer and/or access tools to retrieve and store data from the shared collection to campus-level resources for analysis and computational activities outside of XSEDE.</p> <p>2. Some or all data may be available to any user without permissions restrictions.</p>
<i>Quality Attributes</i>	<p>When a failure or temporary interruption of network access to one or more XSEDE sites occurs, the shared data resource remains readable, to users at unaffected sites for up to 8-12 hours.</p> <p>Storage and retrieval of data can is not limited to a single user or site at any one time, i.e. parallel data access can occur both on a node and a site level.</p> <p>No collection- or project-specific software or tools are required to store or retrieve data from the shared collection.</p>
<i>Non-functional (optional)</i>	
<i>Issues</i>	List of issues that remain to be resolved

<b>Use Case 2.0</b>	<b>UCDM2.0: Coordinated computation and analysis involving a shared body of data</b>
<i>Description</i>	A user or group of users executes a coordinated program of research involving multiple computational, analysis, and visualization tasks executing on multiple XSEDE resources and SPs, utilizing a common body of data.
<i>References</i>	References and citations relevant to use case: TBD.
<i>Actors</i>	<p>Investigator: An individual user who initiates tasks as part of a coordinated research program</p> <p>User Agent: A script or function that acts on behalf of a user on one or more XSEDE resources.</p>
<i>Prerequisites (Dependencies) &amp; Assumptions</i>	<p>All users/investigators have XSEDE or other identities by which permissions can be set and enforced.</p> <p>All users/investigators are part of a single XSEDE allocation that represents</p>

	<p>the program of research.</p> <p>All resources on which users access data are within the XSEDE “circle of trust” and use the XSEDE accounting system to exchange information regarding usage, accounts, and allocations.</p>
<i>Steps</i>	<ol style="list-style-type: none"> <li>1. A user logs in to an XSEDE resource</li> <li>2. The user constructs a job making use of some shared data element accessible on all XSEDE resources</li> <li>3. The user submits the job for execution on a specific XSEDE resource</li> <li>4. The job executes, accessing the shared data element and producing output written to the common data location</li> <li>5. The same or a different user logs in to a different resource</li> <li>6. The user constructs a job making use of data produced as the output of step 4</li> <li>7. The user submits the job for execution on a specific XSEDE resource</li> <li>8. The job executes, reading in the output of step 4 and further producing output for users in subsequent tasks</li> <li>9. Steps 5 through 8 are repeated by the same or different users</li> </ol>
<i>Variations (optional)</i>	<ol style="list-style-type: none"> <li>1. Instead of a specific resource, users may use the XSEDE user portal, a science gateway, or another indirect mechanism for constructing and submitting jobs for execution.</li> <li>2. Some output data elements may be “open”, i.e. not subject to permissions restrictions</li> </ol>
<i>Quality Attributes</i>	<p>When a failure or temporary interruption of network access to one or more XSEDE sites occurs, the shared data resource remains available to users at unaffected sites for 8-12 hours.</p> <p>Storage and retrieval of data can is not limited to a single user or site at any one time, i.e. parallel data access can occur both on a node and a site level.</p>
<i>Non-functional (optional)</i>	
<i>Issues</i>	List of issues that remain to be resolved

<b>Use Case 3.0</b>	<b>UCDM3.0: Shared use of large-scale/streaming sensor input data</b>
---------------------	-----------------------------------------------------------------------

<i>Description</i>	A group of users, individually or collectively, perform a set of computations or analyses using input data uploaded on a periodic or continuous basis from a sensor or system of sensors.
<i>References</i>	References and citations relevant to use case: TBD.
<i>Actors</i>	<p>Sensor: A system making observations of some phenomena of research interest, such as a telescope, a weather station, or a seismograph</p> <p>Input gateway: A system enabling the storage of data from a sensor into an XSEDE data resource on a continuous basis</p> <p>User agent: A software agent acting on behalf of the user to retrieve and/or transform data deposited by the sensor on the user's behalf</p> <p>Input agent: A software agent automating the storage of data from a sensor into an XSEDE data resource on a continuous or periodic basis</p>
<i>Prerequisites (Dependencies) &amp; Assumptions</i>	<p>All users of the sensor data have XSEDE accounts and are members of a single project or group used to define shared permission to access input data.</p> <p>The users or project managers have independently established access to one or more XSEDE resources for the purpose of automating data retrieval by the input gateway</p> <p>All resources on which users access data are within the XSEDE "circle of trust" and use the XSEDE accounting system to exchange information regarding usage, accounts, and allocations.</p>
<i>Steps</i>	<ol style="list-style-type: none"> <li>1. A user logs in to an XSEDE resource.</li> <li>2. A user constructs a job making use of sensor input data, using variables or another mechanism to allow for selection of an input "window" in time or space.</li> <li>3. The user submits and successfully tests the job execution with exemplary input data</li> <li>4. The user makes this job available to others on the same or other resources.</li> <li>5. An input agent retrieves new data from or through the input gateway, either continuously or on a regular, e.g. daily, basis.</li> <li>6. One or more users reuse the job script from step 3 with the data from step 5.</li> <li>7. The data resulting from step 6 may be further shared as in UCDM 1.0</li> </ol>
<i>Variations (optional)</i>	<ol style="list-style-type: none"> <li>1. Users may not always reuse the same job scripts with varying input</li> </ol>

	<p>data. Instead both the job and the input data may vary.</p> <ol style="list-style-type: none"> <li>Jobs could be created and launched on behalf of a science gateway, or could be launched automatically to process data as it is created.</li> <li>Jobs could be run on campus level resources with XSEDE services being used only to provide access to the shared data resource.</li> </ol>
<i>Quality Attributes</i>	<p>Successful storage of 95% or more of all sensor outputs successfully sent to the input agent (i.e. not experiencing a failure outside of XSEDE).</p> <p>Successful execution of 95% or more of tasks accessing the sensor data once it has been successfully retrieved and stored.</p> <p>Overall performance sufficient to retrieve results with a continuous generation rate of up to 10MB/sec.</p>
<i>Non-functional (optional)</i>	
<i>Issues</i>	List of issues that remain to be resolved

<b>Use Case 4.0</b>	<b>UCDM4.0: Migration of data between resources</b>
<i>Description</i>	A user or project migrates all their active data to a new resource, either because of a change in allocation status or the introduction of a new resource into the XSEDE ecosystem.
<i>References</i>	References and citations relevant to use case: TBD.
<i>Actors</i>	<p>Data owner: The “owner” or responsible party for a working set of data.</p> <p>User agent: A software agent acting on behalf of the user to copy or move data between resources and/or sites.</p> <p>Data Transfer service: a service or collection of services, running as a daemon on the source and destination resources, which provide data transfer functionality in conjunction with the user agent.</p>

<i>Prerequisites (Dependencies) &amp; Assumptions</i>	<p>The user has existing allocations for resource access, and any required storage allocations, on both the source and destination resource.</p> <p>The data to be migrated is within reasonable parameters for the size of data relative to network capacity and target file system capacity.</p>
<i>Steps</i>	<ol style="list-style-type: none"> <li>1. The data owner identifies project folders of importance to their ongoing efforts.</li> <li>2. The data owner initiates a command or script to perform data transfer operations on a collection of files and/or folders.</li> <li>3. Data is transferred by the user agent to the destination resource, and verification is performed.</li> <li>4. When data transfer is complete for all identified data, notification is sent to the user of the completion of the transfer process.</li> </ol>
<i>Variations (optional)</i>	<ol style="list-style-type: none"> <li>1. There may be a period during which data is in use on two separate resources, and must be synchronized on a regular basis.</li> <li>2. Identification of the data to be migrated could be automated based on storage allocation information, default migration of home directories, or another automatic selection process for data migration.</li> </ol>
<i>Quality Attributes</i>	<p>The data owner must perform no more than 1 initiation step per file system (or equivalent storage resource) from/to which data will be migrated.</p> <p>100% of data must be successfully transferred between resources and verified.</p> <p>Data that fails to be transferred or to be verified post-transfer is retransferred automatically.</p>
<i>Non-functional (optional)</i>	
<i>Issues</i>	List of issues that remain to be resolved